



## RAVENOL ATF M 6-Serie

### ATF Professional Line

RAVENOL ATF M 6-Serie is automatic transmission oil, produced on the basis of hydrocrack oils and PAO with special additives and inhibition which guarantees a perfect function of the automatic transmission.

RAVENOL ATF M 6-Serie is one of the ATF (Automatic Transmission Fluid) of the newly developed generation for 5-motion automatic transmission with converter lock-up clutch AG 722.6 und AG 722.7 of Mercedes-Benz. A maximum wear protection in every operating state is guaranteed.

### Application Notes

RAVENOL ATF M 6-Serie was developed for use in 5-motion transmission with converter lock-up clutch AG 722.6 und AG 722.7 of Mercedes-Benz.

### Quality Classifications

#### Approvals

MB-Approval 236.10 (A 001 989 21 03)

#### Practice and tested in aggregates with filling

Chrysler 52107891AA

### Characteristic

RAVENOL ATF M 6-Serie offers:

- a very good lubricating ability even at low temperatures in winter
  - a high, stable viscosity index
  - a very low pour point
  - a very good oxidation stability
  - as far as possible protection against corrosion and foam formation
  - good balanced coefficient of friction
  - a neutral behaviour against sealing materials
  - a neutral behaviour because of inhibition against non-ferrous metals
- 
- RAVENOL special transmission fluid is special development for special gear and cannot be selected on the basis of technical parameters (viscosity, etc.). Therefore the decision was made not to give technical data.
  - **Please note:** RAVENOL special transmission fluid is exclusively to apply under the original number, as indicated in the product information. Not sure of the correct transmission fluid, you can ask your garage or the car dealer with respect to the original OEM gear type and number or consult our advisers. It must be specified the VIN code (Vehicle Identification Number) of your vehicle.
  - Misapplication of RAVENOL special transmission fluid can lead to malfunction of the transmission shifting problems, increased fuel consumption, unwanted slip behavior, etc. cause and cause the failure of the transmission.
  - Ravensberger Schmierstoffvertrieb GmbH does not liable for transmission failures in case of wrong selection of RAVENOL special transmission fluid.

Characteristics	Unit	Data	Audit
Colour		rot	visual
Density at 20°C	kg/m <sup>3</sup>	847	EN ISO 12185
Pourpoint	°C	-51	DIN ISO 3016

All indicated data are approximate values and are subject to the commercial fluctuations.

All information correspond to the best of our knowledge to the actual situation of the cognitions and our development. Subject to alterations. All references made to DIN-norms are only for the description of the goods. There is no guarantee. In case there will be any problems please contact the technical service.

19.08.2016

Ravensberger Schmierstoffvertrieb GmbH

Postfach 1163

33819 Werther

Tel.: 05203/9719-0

Fax.: 052039719-40 / 41