



RAVENOL CVT Fluid

RAVENOL CVT Fluid is a fully synthetic ATF for the latest generation of CVT transmission.

RAVENOL CVT Fluid guarantees an optimum of power transmission.

RAVENOL CVT Fluid is based on fully synthetic oil (PAO) with a special additive and inhibition to ensure the proper operation of the automatic transmission.

Application Notes

RAVENOL CVT Fluid was developed for use in CVT transmission (Steel Belt Continuously Variable Transmission).

RAVENOL CVT Fluid ensures a stable viscosity under high mechanical stress in the transmission elements (push belt).

Quality Classifications

RAVENOL CVT Fluid corresponds to:

Practice and tested in aggregates with filling

BMW CVT EZL 799A, Ford EU WSS-M2C928-A, Focus C-Max CFT23, Ford USA WSS-M2C933-A, XT-7-QCFT Freestyle, Five Hundred CFT30, Honda CVT Fluid 08200-9006, HMMF Ultra Fluid 08260-99904, 08260-99907, MB 236.20 A 0019894603, Mazda TFF CVT Fluid TC JWS3320 K020-W0-051W, Nissan CVT Fluid NS-1, KLE50 00002, KLE50 00004, Opel/GM 1940713, Subaru i-CVT Fluid K0415-YA090, Suzuki S-CVT 99000-22801-000, Toyota CVT Fluid TC 08886-02105, VW/AUDI G052180A1/A2/A6, TL 52180, VW G 052 516 A2, Mini Cooper CVT

Characteristic

RAVENOL CVT Fluid offers:

- Very good lubricating ability even at low temperatures in winter
- A high, stable viscosity index
- Very low pour point
- Very good oxidation stability
- Protection against corrosion and foam formation
- Good balanced coefficient of friction
- Neutral behaviour towards sealing materials
- Neutral behaviour by inhibition to non-ferrous metals

Characteristics	Unit	Data	Audit
Colour		braun	-
Density at 15°C	kg/m ³	854	EN ISO 12185
Pourpoint	°C	-51	DIN ISO 3016

All indicated data are approximate values and are subject to the commercial fluctuations.

All information correspond to the best of our knowledge to the actual situation of the cognitions and our development. Subject to alterations. All references made to DIN-norms are only for the description of the goods. There is no guarantee. In case there will be any problems please contact the technical service.

26.07.2016

Ravensberger Schmierstoffvertrieb GmbH

Postfach 1163

33819 Werther

Tel.: 05203/9719-0

Fax.: 052039719-40 / 41