



RAVENOL Getriebeöl TGO SAE 75W-90 API GL 5

RAVENOL Getriebeöl TGO SAE 75W-90 API GL 5 is a semi-synthetic transmission oil specifically for maximum duty hypoid geared transmissions.

RAVENOL Getriebeöl TGO SAE 75W-90 API GL 5 is designed based on high-quality solvent refined and synthetic base oils and specially harmonised additive treatment with extreme pressure (EP) active ingredients and other additives. This exceeds the needs of today's application requirements.

Application Notes

RAVENOL Getriebeöl TGO SAE 75W-90 API GL 5 is a maximum duty transmission oil for use in maximum duty, hypoid geared transmissions (axle drives, manual transmissions, etc.), where maximum duty transmission oils are required.

Quality Classifications

Specifications

API GL-5, MIL-L-2105 D

Practice and tested in aggregates with filling

Ford M2C-9002A, ZF TE-ML 05A, ZF TE-ML 07A, ZF TE-ML 17B, CS 3000B, Mack GO-G, GM, MB 235.0, MB 235.1

Characteristic

RAVENOL Getriebeöl TGO SAE 75W-90 API GL 5 offers:

- Excellent oxidation stability.
- Greatest possible protection from rust, corrosion, foaming.
- Low solidification point.
- Excellent extreme pressure (EP) properties.
- High viscosity index.
- Fuel savings.

Characteristics	Unit	Data	Audit
Colour		gelbbraun	-
Density at 20°C	kg/m ³	870	EN ISO 12185
Viscosity at 40°C	mm ² /s	83	DIN 51 562
Viscosity at 100°C	mm ² /s	15	DIN 51 562
Viscosity index VI		193	DIN ISO 2909
Flash point (COC)	°C	>180	DIN ISO 2592
Pourpoint	°C	-33	DIN ISO 3016

All indicated data are approximate values and are subject to the commercial fluctuations.

All information correspond to the best of our knowledge to the actual situation of the cognitions and our development. Subject to alterations. All references made to DIN-norms are only for the description of the goods. There is no guarantee. In case there will be any problems please contact the technical service.

27.07.2016

Ravensberger Schmierstoffvertrieb GmbH

Postfach 1163

33819 Werther

Tel.: 05203/9719-0

Fax.: 052039719-40 / 41