



RAVENOL Hydraulik PSF Fluid

RAVENOL Hydraulik PSF Fluid is a specific synthetic hydraulic fluid for power steering.

RAVENOL Hydraulik PSF Fluid is guaranteeing an optimized power transmission.

RAVENOL Hydraulik PSF Fluid is produced on the basis of high quality base oils with special additives and inhibition which guarantees a perfect function of the hydraulics.

Application Notes

RAVENOL Hydraulik PSF Fluid is especially developed for the use as a hydraulic fluid in power transmissions.

Quality Classifications

Practice and tested in aggregates with filling

Honda PSF-S, Hyundai PSF-3, KIA PSF-III, Mazda PSF, Subaru PS Fluid, TOYOTA PSF-EH, CITROËN/PEUGEOT 9735EJ für C-Crosser und PEUGEOT 4007, MITSUBISHI DIAMOND PSF-2M

Characteristic

RAVENOL Hydraulik PSF Fluid offers:

- A very low pour point
- An excellent foam prevention, no foam formation
- A good lubricating ability even at low temperatures in winter
- A high, stable viscosity index
- A very good oxidation stability
- Excellent protection against wear and tear, corrosion and foam formation
- Fine tuned coefficient of friction
- Neutral behaviour against sealing materials
- Neutral behaviour because of inhibition against non ferrous metals

Characteristics	Unit	Data	Audit
Colour		red	visual
Density at 20°C	kg/m ³	854	EN ISO 12185
Viscosity at -40°C	mPa*s	15.750	ASTM D5293
Viscosity at 40°C	mm ² /s	34,8	DIN 51 562
Viscosity at 100°C	mm ² /s	7,2	DIN 51 562
Viscosity index VI		178	DIN ISO 2909
Flash point (COC)	°C	211	DIN ISO 2592
Pourpoint	°C	-48	DIN ISO 3016

All indicated data are approximate values and are subject to the commercial fluctuations.

All information correspond to the best of our knowledge to the actual situation of the cognitions and our development. Subject to alterations. All references made to DIN-norms are only for the description of the goods. There is no guarantee. In case there will be any problems please contact the technical service.

26.07.2016

Ravensberger Schmierstoffvertrieb GmbH

Postfach 1163

33819 Werther

Tel.: 05203/9719-0

Fax.: 052039719-40 / 41